

Amendments to the Claims:

1. (previously presented) An optical recording system for burning an optical disc, the optical recording system comprising:

a housing;

5 a laser pickup installed inside the housing for writing data onto the optical disc according to a write strategy and reading an RF signal from the optical disc;

a laser drive installed inside the housing connected to the laser pickup for controlling operations of the laser pickup;

10 a read channel installed inside the housing connected to the laser pickup for processing the RF signal received by the laser pickup;

a jitter meter installed inside the housing connected to the read channel for generating delay signals according to the processed RF signal; and

15 a digital signal processor installed inside the housing connected to the laser drive and the jitter meter for receiving the delay signals, configuring the write strategy according to the delay signals, and controlling the laser drive to control the laser pickup to write data onto the optical disc according to the configured write strategy;

wherein the jitter meter includes:

20 a delay chain having a plurality of delay cells connected in a cascade manner, each delay cell delaying an input signal a time unit;

a buffer set connected to the delay chain for storing a delay signal received from the delay chain, the buffer set having a plurality of buffers each connected to a delay cell for receiving a delay bit of the delay signal transmitted from the delay cell; and

25 a control unit connected to the read channel and the buffer set for outputting a control signal according to a standard clock and the processed RF signal.

2. (canceled)

3. (canceled)

4. (previously presented) The optical recording system of claim 1 wherein each of the
5 delay cells is a flip-flop.

5. (original) The optical recording system of claim 4 wherein the flip-flop is either
rising-edge triggered or falling-edge triggered.

10 6. (original) The optical recording system of claim 1 wherein the optical disc
comprises a lead-in area, the processed RF signal sent to the jitter meter being
generated from an RF signal read from the lead-in area of the optical disc.

15 7. (original) The optical recording system of claim 1 further comprising firmware for
storing parameters and arithmetic formula.

8. (currently amended) A method for burning an optical disc in an optical recording
system comprising the following steps:

20 (a) writing data onto the optical disc according to a write strategy and reading an
RF signal from the optical disc;

(b) processing the RF signal;

(c) generating delay signals according to the processed RF signal by:

delaying the processed RF signal;

outputting a control signal according to a standard clock and the processed

25 RF signal; and

generating a delay signal according to the control signal and the delayed

RF signals; and

(d) configuring the write strategy according to the delay signals;

wherein the delay signal is formed by a plurality of delay bits received from a plurality of buffers, each buffer connected to a delay cell from a plurality of delay cells, the plurality of delay cells being connected in a cascade manner.

- 5 9. (canceled)
10. (canceled)
11. (original) The method of claim 8 wherein the RF signal is read from a lead-in area
10 of the optical disc.
12. (previously presented) The method of claim 8 wherein the write strategy in step (d) is configured according to the material and manufacturer of the optical disc.
- 15 13. (previously presented) An optical recording system for burning an optical disc, the optical recording system comprising:
- a housing;
- a laser pickup installed inside the housing for writing data onto the optical disc
 according to a write strategy and reading an RF signal from the optical disc;
- 20 a laser drive installed inside the housing connected to the laser pickup for
 controlling operations of the laser pickup;
- a read channel installed inside the housing connected to the laser pickup for
 processing the RF signal received by the laser pickup;
- 25 a jitter meter installed inside the housing connected to the read channel for
 generating delay signals according to the processed RF signal; and
- a digital signal processor installed inside the housing connected to the laser drive
 and the jitter meter for receiving the delay signals, configuring the write

strategy according to the delay signals, and controlling the laser drive to control the laser pickup to write data onto the optical disc according to the configured write strategy;

wherein the jitter meter includes:

- 5 a delay chain having a plurality of delay cells connected in a cascade manner, wherein the processed RF signal is coupled to a clock input of a first delay cell, and an output of each delay cell is coupled to a clock input of a following delay cell, each delay cell delaying an input signal a time unit;
- 10 a buffer set connected to the delay chain for storing a delay signal received from the delay chain; and
- a control unit connected to the read channel and the buffer set for outputting a control signal according to a standard clock and the processed RF signal.

14. (previously presented) The optical recording system of claim 13 wherein the buffer
15 set comprises a plurality of buffers each connected to a delay cell for receiving a delay bit of the delay signal transmitted from the delay cell.

15. (previously presented) A method for burning an optical disc in an optical recording
system comprising:
- 20 (a) writing data onto the optical disc according to a write strategy and reading an RF signal from the optical disc;
- (b) processing the RF signal;
- (c) generating delay signals according to the processed RF signal by:
- 25 delaying the processed RF signal with a delay chain having a plurality of delay cells connected in a cascade manner, the processed RF signal coupled to a clock input of a first delay cell, and an output of each delay cell coupled to a clock input of a following delay cell;
- outputting a control signal according to a standard clock and the processed

RF signal; and
generating a delay signal according to the control signal and the delayed
RF signals; and

(d) configuring the write strategy according to the delay signals.

5

16. (previously presented) The method of claim 15 wherein the delay signal is formed by
a plurality of delay bits received from a plurality of buffers, each buffer connected to a
delay cell.

10

15

20

25